

SAMSUNG



Crystal UHD Signage

QMC series

Slim design. Stunning performance.

Introducing the QMC series, the slimmest display in the Samsung's UHD signage offerings. This products deliver an unparalleled slim design that fits into any business, while delivering the visual quality to make a big impact. The sleek form factor is easily installed to fit any room design and delivers stunning visual performance. Dynamic Crystal Color and Quantum Processor Lite 4K delivering consistent, lifelike colors to any content. This is not just a display for simple advertising. It's a display that brings the solutions, tools, and picture quality to grow to your business, no matter what industry you're in.

Key features



Ultra Slim Depth

The unparalleled ultra-slim thickness of 28.5mm makes it the thinnest option in Samsung's UHD Signage series. It comes with the Slim Fit Wall Mount, which allows you to install it neatly and easily in any environment.



Even Bezels and Centered VESA Holes

The bezels are even on all four sides of the display for a consistent look, while the central VESA mounting holes ensure secure mounting and easy adjustability to portrait mode.



Dynamic Crystal Color

One billion shades of color let you see every subtlety with lifelike color variations. Images are clear and consistent thanks to Samsung's industry leading video processing and upscaling technology.



Smartview+

In the QMC series, SmartView+ enables wireless screen sharing for easy collaboration and quick screen switching with just a click.



Smart Calibration

Guarantee complete brand consistency across every location. Using the Samsung mobile app, calibrate displays to showcase brand logos and other collateral in the exact colors required.



Energy Star / EPEAT Bronze / TÜV Rheinland Carbon Footprint

Samsung is making diverse efforts to reduce our environmental impact in smart signage, and encouraging users to pursue a more sustainable life.

Specifications

Model			QM43C	QM50C	QM55C	QM65C	QM75C	QM85C
Display Panel	Diagonal Size	Class	43	50	55	65	75	85
		Measured	42.5	48.5	54.6	64.5	74.5	84.5
	Resolution		3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)
	Brightness (Typ.)		500 nit	500 nit	500 nit	500 nit	500 nit	500 nit
	Orientation		Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait
	Haze		25%	25%	25%	25%	25%	25%
	Contrast Ratio (Typ.)		4,000:1 (* IPS -1,200:1)	4,000:1 (* IPS -1,200:1)	4,000:1	4,000:1	4,000:1	4,000:1
	Type		VA/IPS	VA/IPS	VA	VA	VA	VA
	Active Display Area		941.84 (H) x 529.416 (V)	1,095.84 (H) x 616.4 (V)	1,209.6 (H) x 680.4 (V)	1,428.48 (H) x 803.52 (V)	1,650.24 (H) x 928.26 (V)	1,872.0 (H) x 1,053.01 (V)
Pixel Pitch (mm)		0.245 x 0.245	0.285 x 0.285	0.315 x 0.315	0.372 x 0.372	0.429 x 0.429	0.487 x 0.487	
Color Gamut		NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	
Operation Hour		24/7	24/7	24/7	24/7	24/7	24/7	
Connectivity / Sound	Input	Video	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)
		Audio	N/A	N/A	N/A	N/A	N/A	N/A
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
		Tuner	N/A	N/A	N/A	N/A	N/A	N/A
	Output	Video	N/A	N/A	N/A	N/A	N/A	N/A
		Audio	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
		USB	N/A	N/A	N/A	N/A	N/A	N/A
	WiFi / BT		O/O	O/O	O/O	O/O	O/O	O/O
	External Control		RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45
Speaker		10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch	
Mechanical Spec	Dimension (mm)	Set	969.5 x 557.8 x 28.5	1,124.1 x 644.8 x 28.5	1,237.9 x 708.8 x 28.5	1,456.8 x 831.9 x 28.5	1,682.3 x 960.4 x 28.5	1,904.3 x 1085.3 x 28.5
		Package	TBD	TBD	TBD	TBD	TBD	TBD
	Weight (kg)	Set	TBD	TBD	TBD	TBD	TBD	TBD
		Package	TBD	TBD	TBD	TBD	TBD	TBD
	VESA Mount		200 x 200	200 x 200	200 x 200	400 x 300	400 x 400	400 x 400
	VESA Mount Screw (Min~Max)		M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm
Bezel Width (mm)		11.5 (Even)	11.5 (Even)	11.5 (Even)	11.5 (Even)	13.4 (Even)	13.9 (Even)	
Features	Key		UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0
	Internal Player	Operating System	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0
		Processor	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core
		Storage (FDM)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)
	H/W	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR
		Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor
		Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor
	Special	Auto Level	Auto Level	Auto Level	Auto Level	Auto Level	Auto Level	Auto Level
		Wi-Fi (2.4/5.0GHz dual) and BT		Wi-Fi (2.4/5.0GHz dual) and BT	Wi-Fi (2.4/5.0GHz dual) and BT	Wi-Fi (2.4/5.0GHz dual) and BT	Wi-Fi (2.4/5.0GHz dual) and BT	Wi-Fi (2.4/5.0GHz dual) and BT
Signage New Home Workspace (Microsoft371/VMWare/RDP)		Signage New Home Workspace (Microsoft371/VMWare/RDP)	Signage New Home Workspace (Microsoft371/VMWare/RDP)	Signage New Home Workspace (Microsoft371/VMWare/RDP)	Signage New Home Workspace (Microsoft371/VMWare/RDP)	Signage New Home Workspace (Microsoft371/VMWare/RDP)	Signage New Home Workspace (Microsoft371/VMWare/RDP)	
Certification	S/W	Custom Home Auto Source	Custom Home Auto Source	Custom Home Auto Source	Custom Home Auto Source	Custom Home Auto Source	Custom Home Auto Source	
		Switching and Recovery	Switching and Recovery	Switching and Recovery	Switching and Recovery	Switching and Recovery	Switching and Recovery	
		Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	
	Director Mode	Director Mode	Director Mode	Director Mode	Director Mode	Director Mode	Director Mode	
		SmartView+	SmartView+	SmartView+	SmartView+	SmartView+	SmartView+	
		Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	
	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform		
	Video Conference Solution	Video Conference Solution	Video Conference Solution	Video Conference Solution	Video Conference Solution	Video Conference Solution		
	Smart Calibration	Smart Calibration	Smart Calibration	Smart Calibration	Smart Calibration	Smart Calibration		
Safety	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1		
EMC	Class B	Class B	Class B	Class B	Class B	Class A		
Environment	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT		
IP Rating	IP5x	IP5x	IP5x	IP5x	IP5x	IP5x		
Security	802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	802.1 x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP		
PowerSupply	AC 100 - 240 V, 50/60 Hz	AC 100 - 240 V, 50/60 Hz	AC 100 - 240 V, 50/60 Hz	AC 100 - 240 V, 50/60 Hz	AC 100 - 240 V, 50/60 Hz	AC 100 - 240 V, 50/60 Hz		
Power	Power Consumption	Max[W/h]	TBD	TBD	TBD	TBD	TBD	
	Typical[W/h]	TBD	TBD	TBD	TBD	TBD	TBD	
Operating Condition	Sleep mode		less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	
	Temperature	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C	
Relative Humidity		10~80%	10~80%	10~80%	10~80%	10~80%	10~80%	
Accessories	Included		Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord
	Included		RS232C (In) Gender	RS232C (In) Gender	RS232C (In) Gender	RS232C (In) Gender	RS232C (In) Gender	RS232C (In) Gender
	Remote Controller and Batteries		Remote Controller and Batteries	Remote Controller and Batteries	Remote Controller and Batteries	Remote Controller and Batteries	Remote Controller and Batteries	Remote Controller and Batteries
	Optional	Stand Mount Specialty	STN-L4355C	STN-L4355C	STN-L4355C	STN-L6585C	STN-L6585C	STN-L6585C
		WMN-B505C	WMN-B505C	WMN-B505C	WMN-B505C	WMN-B505C	N/A	
		TBD	TBD	TBD	TBD	TBD	TBD	

Learn More

Product Support

Follow Us

samsung.com/display

samsung.com/business

insights.samsung.com

1-866-SAM4BIZ

 youtube.com/samsungbizusa

 @SamsungBizUSA

