



SOLIDS TATE DRIVE


Unidad de Estado Sólido





SOLIDS TATE DRIVE

Unidad de Estado Sólido





SOLIDS TATE DRIVE

Unidad de Estado Sólido

Soporta funciones S.M.A.R.T., Trim Command, NCQ
Corrección de errores configurable, o Sobreprovisionamiento configurable por el usuario.
Avanzada tecnología de nivelación de desgaste.

Especificaciones

Interfaz	SATA III	Voltaje	DC 5V
Dimensiones	100 X 69.9 X 7 cm	Temperatura de funcionamiento	0°C~70°C
		4Kb Random Read IOPS	70000
		4KBb Random Write IOPS	5000

Medidas 12 x 10 2.3 cm Peso de producto 300gr Corrugado Depende la piezas



SOLIDS TATE DRIVE

Unidad de Estado Sólido



120 Gb

Sequential Read:	500MB/s
Sequential Write:	450MB/s
Response Time:	0.2ms

480 Gb

Sequential Read:	500MB/s
Sequential Write:	450MB/s
Response Time:	0.2ms

240 Gb

Sequential Read:	500MB/s
Sequential Write:	450MB/s
Response Time:	0.2ms

1Tb

Sequential Read:	500MB/s
Sequential Write:	450MB/s
Response Time:	0.2ms

	SKU	Ean13
Modelo:	120Gb STMSSD1B	7503028126699
	240Gb STMSSD2B	7503028126705
	480Gb STMSSD3B	7503028126712
	1Tb STMSSD4B	7503041018292

Dun14