

ThinkPad Wireless Mouse | Part Number: 4X30M56887

 lenovo.com/ca/en/accessories-and-monitors/keyboards-and-mice/mice/KB-MICE-BO-ThinkPad-Wireless-Mouse/p/4X30M56887

- Overview

The ThinkPad Essential Wireless Mouse is an excellent choice as a travel-sized wireless mouse. This sleek and stylish travel-size design offers exceptional quality in a modern wireless solution. The compact ambidextrous mouse provides excellent portability and perfect ergonomics.

Features & Benefits

- Precise 1200 dpi optical sensor.
- Connect compatible Lenovo devices with just 1 nano receiver.
- 3 Buttons (1) Left click, (2) Right click, (3) Click wheel
- Ambidextrous design for both left and right hand comfort
- 1 AA battery for 12 months battery life

- Tech Specs

Color	Black
Battery Life	Up to 12 months
Connection Type	2.4 GHz Wireless via Nano USB
Weight	60 g (0.13 lbs)
Special Design Features	Ambidextrous design
Mice Button	3 (left click, right click, scroll click)
DPI	1200 DPI
Mouse Sensor	Optical sensor
Hardware Requirements	Supported PC with USB port
Power Requirement	1 AA battery
Scrolling	Scroll Wheel (up/down/left/right)
Brand	ThinkPad
OS Requirements	Windows 7, Windows 8, Windows 10
Agency Approvals	ANATEL, BIS, BSMI, CB, CE, CE, CITC, CNC, CONATEL, cTUVus, EAC, ETA, FCC, IC, ICASA, IFETEL, IMDA, KCC, MIC, MOC, NCC, NTC, NTRA, RCM, SDPPI, SIRIM, SRRC, SUBTEL, TRA, TUV Mark
Package Type	Brown box
Height	33 mm (1.30 in)
Length	61 mm (2.40 in)
Depth	106 mm (4.17 in)
Warranty Period	1 Year
Maximum Operating Temperature	40 degrees Celsius (104 degrees Fahrenheit)

Minimum Operating Temperature	0 degrees Celsius (32 degrees Fahrenheit)
Maximum Relative Humidity (%)	95%
Minimum Relative Humidity (%)	20%
Shipment Group	ThinkPad Essential Wireless Mouse; Nano USB receiver; 1 AA battery; Set-up and information poster
Connections	
Pointing Device Resolution	1200 DPI
Pointing Device Type	ThinkPad Wireless Mouse
Number of Buttons	3
Height	33 mm
Width	61.08 mm
Depth	106 mm
Weight	0.06 kg
Min Operating Humidity	20%
Max Operating Humidity	95%
Min Operating Temperature	0 C
Max Operating Temperature	40 C
Warranty Types	1 Year - Customer Replaceable Unit
Warranty Period	One year
