

HOGAR		HOGAR INTELIGENTE	NEGOCIOS	SERVICE PROVIDER
CARACTERÍSTICAS DE HARDWARE				
Interface		USB 2.0		
LED		Status		
Dimensiones		26.8 × 15.7 × 7.5 mm (1.06 × 0.62 × 0.30 in)		
Antena		2× Dual-Band Antennas		
CARACTERÍSTICAS INALÁMBRICAS				
Estándares Inalámbricos		IEEE 802.11a/b/g/n/ac/ax		
Tasa de Señal		5 GHz: 11ax: Up to 1201 Mbps(dynamic) 11ac: Up to 867 Mbps(dynamic) 11n: Up to 300 Mbps(dynamic) 11a: Up to 54 Mbps(dynamic) 2.4 GHz: 11ax: Up to 574 Mbps(dynamic) 11n: Up to 400 Mbps(dynamic) 11g: Up to 54 Mbps(dynamic) 11b: Up to 11 Mbps(dynamic)		
Potencia de Transmision		5 GHz: 10dBm(FCC) 2.4 GHz : 10dBm(FCC)		
Modos Inalámbricos		Infrastructure mode		
Seguridad Inalámbrica		WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK		
OTROS				
Certificacion		FCC, CE, RoHS		
Contenidos del Paquete		AX1800 Nano Wi-Fi 6 Wireless USB Adapter TX20U Nano Quick Installation Guide		
Requisitos del Sistema		Supported operating systems include Windows 10, 11		
Ambiente		Operating Temperature: 0°C~40°C (32°F ~104°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing		

Para obtener información adicional sobre la versión, vaya a la [página de soporte](#).

*Models' appearances and specifications are not determined and will be updated accordingly. Please use the product images only for reference.

**Some features may require software upgrades or subscriptions.

****Use of Wi-Fi 6 and other features, including OFDMA and MU-MIMO, require your APs to also support the corresponding features.