

DC-2300: A brilliant Card Printer



Modular Direct to Card Printers at 300 x 1200 DPI

- Space-saving modular design
- Easy to install ribbon cartridge.
- High throughput with up to 180 cards per hour
- Excellent print resolution
- Card feeder with 100 card capacity
- Multiple modes of use with optional Duplexer




DASCOM introduces evolutionary technology with the DC-2300 series Card Printer that adapts to your business needs while helping you be more productive at a cost-effective price.

The Printer's direct to card technology generates brilliant, high resolution colors and includes DASCOM Security options with optional holographic capability for enhanced security. These security features help to mitigate compromise of your important business data and cards.

The printer's modular design allows you to print dual-sided with an optional Duplexer without compromising its small footprint size.

The DC-2300 can be used with other business card software, or as a traditional Windows Printer.



New easy to load Ribbon Cartridge

Available configurations:

Single-Sided Model - 28.883.6183

Dual-Sided Model - 28.883.6179

DC-2300: A brilliant Card Printer

Print speed	YMCKO Ribbon, single side: 180 cards per hour YMCKO Ribbon, double side: 90 cards per hour K only Ribbon, single side: 450 cards per hour
Printing Capability	Single Side, Edge-to-Edge, optional Dual-Sided
Resolution	300 dpi with possibility of 300x600 dpi and 300x1200 dpi
Options	Duplexer, Contact, Contactless, Mag Strip Encoding
Feeder capacity	100 cards 0.76 mm thick
Card thickness	0.25 ~ 1.25mm
Printing method	Dye-sublimation direct to card technology.
Memory	RAM: 32MB, ROM: 2MB + 4MB
Processor	Integrated Circuit / STMicroelectronics
Graphics processor	FPGA/ Lattice Semiconductor
Safety features	Proprietary DASCOM SOCTechnology, Custom Watermarks, RFID Encrypted Ribbons, Data Protection using K only Ribbons
Terms of use	15 - 35 ° C. Humidity: 20 - 65%.
Storage conditions	-5 - 70 ° C. Humidity: 35 - 96%.
Dimensions	352 cm × 199 cm × 210 cm (13,85 x 7,83 x 8,26 inches)
Weight	6 kg (13.2 pounds)
Warranty	3-years
Driver	Windows XP, Vista, 7, 8, 10 (32 and 64 bits)
Power supply	100-240 Vac input. 50/60 Hz
Compatible cards	PVC, ABS, PET, PET-G; 85.6 x 53.98 mm (ISO ID-1 / CR-80 size)
Standard interface	USB 2.0, USB host, Ethernet 10/100 Duplex mode
Certifications	FCC SdoC, 2014/53/EU (RED), EMC, ETL, CB + LVD, CCC
Card editing software	Dascom CardEditor.

Printer Options & Consumables

Color Ribbons	YMCKO (500 images), YMCKOO (400), YMCKOK (400), ½YMC KO (600), K only (1650)
Cleaning Set	Cleaning Card, Cleaning Roller and Cleaning Swabs
Options	RFID R/W, SAM R/W, Mag Stripe; Duplexer (dual sided printing)

DASCOM Americas
34 Lakeview Court
Verona, Virginia, 24482 . USA.
Tel: +1 (877) 434-1377
www.dascomamericas.com
info.us@dascom.com

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0
Fax: +49 731 2075-100
info@dascom.com
www.dascomeurope.de

DASCOM (Holdings) LTD
R. 1811-1816A | Nan Fung Centre.
264-298 Castle Peak Road. Tuen Wan,
N. T. | Hong Kong
Tel.: +852 2498 1507
Fax: +852 2413 6047

THERMAL PRINTERS

MOBILE PRINTERS

MATRIX PRINTERS

POS PRINTERS

ID PRINTERS