

VX2729 - 27" 1080P 200HZ 1MS GAMING MONITOR WITH AMD FREESYNC PREMIUM

Key Features


- SuperClear® IPS Panel with 200Hz refresh rate and 1ms (MPRT) response time
- AMD FreeSync™ Premium technology eliminates image tearing
- Stunning Full HD resolution for crisp visuals and immersive gameplay
- Connect your favorite devices with dual HDMI ports and one DisplayPort input




27
DISPLAY



IPS
PANEL



1920x1080
RESOLUTION



RESOLUCIÓN FULL HD
(1920x1080p)

Product Description

Level up the way you watch shows and play games with the 27" ViewSonic® VX2729 Full HD IPS monitor. Featuring a rapid-fire 200Hz refresh rate, 1ms (MPRT) response time and AMD FreeSync™ Premium technology, this 27" monitor virtually eliminates screen tearing and stuttering for a next-level gaming experience. Plus, with a sleek 3-sided frameless design and SuperClear® IPS technology, the VX2729 is ideal for multi-monitor configurations. Two HDMI (v2.0) inputs, and one DisplayPort (v1.4) ensure versatile connectivity to all your essential entertainment devices.

Specifications

More Information


UPC

766907032697

Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	6 bit + FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	2ms
Response Time (MPRT)	1ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	200Hz
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	17W
Eco Mode (optimized)	19W
Consumption (typical)	21W
Consumption (max)	25W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Joystick key: Up, Right, Down, Left, Center; Shortcut, Power
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)

Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	30 ~ 230 KHz
Frequency Vertical	48 ~ 200 Hz
Tilt (Forward/Back)	3° / 21°
Regulations	CSGSus, FCC-B, ICES003, CEC, NOM, Mexico Energy
Net (lbs)	8.3
Net Without Stand (lbs)	7.6
Gross (lbs)	11.9
Net (kg)	3.8
Net Without Stand (kg)	3.5
Gross (kg)	5.4
Packaging (in.)	27.2 x 18.3 x 5.5
Physical (in.)	24.1 x 17.2 x 8.4
Physical Without Stand (in.)	24.1 x 14.1 x 1.9
Packaging (mm)	690 x 465 x 140
Physical (mm)	612.2 x 436.6 x 213.2
Physical Without Stand (mm)	612.2 x 357.2 x 48.1
Package Contents	VX2729 Display, Power Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907032697



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com