

Eaton 5P1550IR

Catalog Number: 5P1550IR

Eaton 5P UPS, 1550 VA, 1100 W, Input: C14, Outputs: (6) C13, Rack, 1U

General specifications



Product Name

Eaton 5P UPS

Catalog Number

5P1550IR

UPC

743172042934

Product Length/Depth

554 mm

Product Height

43.2 mm

Product Width

438 mm

Product Weight

19.36 kg

Compliances

CE Marked

TUV

Certifications

IEC/EN 62040-1

UL 1778

IEC/EN 62040-2

CE

EAC

cTUVus



Powering Business Worldwide

Battery

Runtime graph

\$row.attributeValue.cdata

Battery management

ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection

Battery replacement

User replaceable

Battery quantity

3

Battery rating

12 V / 9 Ah

Battery type

Lead-acid maintenance-free (replaceable)

Extended battery capability

No

Electrical output

Receptacle

(6) C13

Topology

Line-interactive

Wattage

1100 W

VA rating

1550 VA

Output waveform

Sine wave

Voltage

230V

Output power factor

0.7

Output nominal voltage

230V default (200/208/220/230/240V)

Output voltage range

230 V (+6%/-10%)

Output frequency

50/60 Hz

Feed type

1

Electrical input

Input connection

C14

Input nominal voltage

230V default (200/208/220/230/240V)

Input voltage range

160-294 V (adjustable to 150 V-294 V)

Nominal frequency

50-60 Hz

Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode

Communications

Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for remote On/Off and Remote

Power Off

Dry contacts (2 outputs, optocoupler, RJ)

Expansion slots

One slot for optional communication card

Ethernet interface

No

[Includes network card](#)

No

[Software compatibility](#)

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

[User interface](#)

Multilingual graphical LCD display

[Type of interface](#)

Other

[Potential free switch contact](#)

Yes

Environmental

[Altitude](#)

2000 m

[BTU Rating](#)

Online: 225

[Noise level](#)

<40 dB at 1 meter

[Relative humidity](#)

0-90% non-condensing

[Temperature range](#)

0-90% non-condensing

Additional specifications

[Special features](#)

Automatic Voltage

Regulation (AVR)

High-density protection for networks: 1U only

Energy efficient, reduce energy and cooling costs

Delivers clean sinewave output

1 slot for optional com card (Network management card, Relay card or Network and Industrial card)

Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat)

Fully integrates with Eaton Intelligent Power Manager software

1 USB port + 1 serial port

Advanced Battery Management (ABM)

technology to increase battery lifetime

Next-generation graphical LCD display

Hot swappable batteries

Remote reboot and runtime

Resources

[Brochures](#)

[Eaton UPS Services Quick Guide - EN](#)

[Eaton UPS and battery services - EN](#)

[Manuals and user guides](#)

[Eaton 5P UPS Quick Start Guide](#)

optimization thanks to 2
manageable outlet groups

Form factor

Rack

Rack size

1U

Construction type

482.6 mm (19 inch) device

Enclosure

Black/silver

Rack mounting kit

Yes

Efficiency

97

Package contents

- Rack-mounting kit
- Cable locking system
- USB cable
- Serial cable
- (2) IEC-IEC cables
- Quickstart guide
- Safety instructions

Phase (input)

1

Phase (output)

1

Auto shutdown function

Yes



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)